

## IN THE CLAIMS

Claims 1-19 (Canceled)

20. (Currently amended) Door, comprising  
with a leaf, which can be moved between an open position and a closed position;  
with a guide element (40), which is fastened to the leaf and which cooperates with a guide rail (20) to guide the movement of the leaf; and  
with a locking device (50), which can be shifted between a release position, in which it allows the movement of the leaf, and a blocking position, in which it opposes the movement of the leaf, the locking device being equipped with a locking element (70), which, when the device is moved into the locking position, comes to rest against a contact surface (25) of the guide rail (20), in which,  
when in the locking position, the locking element (70) can be pressed toward the contact surface (25) by a thrust element, ~~especially by the guide element (40)~~, which is attached to the door leaf, with a pretensioning device (90), which pushes the locking element (70) into the locking position, ~~where~~ such that the locking element, when in the locking position, is located between the thrust element and the guide tail, wherein

the locking device (50) is connected by a tensioning means (100) to a drive device and/or to a counterbalancing device realized in the form of ~~for example~~, a tension or torsion spring arrangement in such a way that the drive device and/or the counterbalancing device can exert a force on it which opposes the pretensioning force of the pretensioning device (90) and pushes the locking device into the release position; and

the locking device (50) has a lever (60), supported so that it can pivot around an axis which is essentially transverse, ~~especially more or less perpendicular~~, to the longitudinal direction of the guide rail (20), which lever can be connected on one side of the pivot axis (43) to the tensioning means (100) and on the other side of the pivot axis (43) to the locking element (70),

wherein the locking element (70) is mounted on the lever (60) so that it can tilt around a tilt axis which is ~~more or less~~ essentially parallel to the pivot axis (43).

21. (Previously presented) Door according to Claim 20, wherein, when the locking device (50) is shifted into the locking position, the locking element (70) can be laid against the guide element (40).

22. (Currently amended) Door according to Claim 21, wherein the locking element (40) has a first, essentially flat contact surface (76), which comes to rest against the contact surface (25) when the device is in the locking position, and a second contact surface (78), which, in the locking position, rests against the guide element (40), where the first contact surface (76) forms an acute angle of preferably less than 30°, and ~~especially of approximately 20°~~, with the second contact surface (78).

23. (Previously presented) Door according to claim 20, wherein the pretensioning device (90) has a torsion spring, which is supported at one end on the lever (60) and at the other end at least indirectly on the door leaf.

24. (Previously presented) Door according to claim 20, wherein the locking device has a support element (82), which is located on the side of the guide rail opposite the guide rail's contact surface.

25. (Previously presented) Door according to Claim 24, wherein the support element (82) is supported so that it can pivot around the pivot axis (43).

26. (Currently amended) Door according to claim 20, wherein the guide element (40) has a support shaft (42), which is ~~more-~~  
~~or-less~~ essentially perpendicular to the longitudinal axis of the guide rail (20) and parallel to the plane of the door leaf, which shaft passes through the lever (60), through the torsion spring (90), and/or through the support element (80).

27. (Previously presented) Door according to claim 20, wherein the locking device (50) can be attached to the door leaf by a bracket element (30).

28. (Previously presented) Door according to Claim 27, wherein the bracket element (30) has a U-shaped profile with a connecting sidepiece (32), which is attached to a boundary surface of the door leaf, and two outer sidepieces (34, 36), through which the support shaft (42) passes.

29. (Previously presented) Door according to claim 20, wherein the locking device (50) is located in the area of the edge of the door leaf which is at the bottom when the door is closed.

30. (Previously presented) Door according to claim 20, wherein the guide element (40) has a guide roller (44), which is supported so that it can rotate around the longitudinal axis of the support shaft (42).

31. (Previously presented) Door according to Claim 30, wherein, in the cross-sectional plane perpendicular to its longitudinal axis, the guide rail (20) has a profile in the shape of a "C" or a "J" and is designed to accept the guide roller (44).

32. (Currently amended) Door according to claim 20, wherein the contact surface (25) is ~~more-or-less~~ essentially parallel to the plane of the door leaf.

33. (Previously presented) Door according to claim 20, wherein the door leaf has a plurality of panels (10), which are arranged next to each other in the direction of door leaf travel and are hinged to each other so that they can pivot around pivot axes which are perpendicular to the direction of door leaf travel.

34. (Currently amended) Locking device for a door according to claim 20 with a locking element (70), which, when in the locking position, is located between a thrust element, ~~especially the guide element (40),~~ which is attached to the door leaf, and the guide rail (20).

35. (New) The door according to claim 20, wherein the locking element (70) can be pressed toward the contact surface (25) by a thrust element and the guide element (40).

36. (New) The door according to claim 22, wherein the angle between the first contact surface (76) and the second contact surface (78) is approximately  $20^{\circ}$ .

37. (New) Locking device for a door according to claim 34 with a locking element (70), which, when in the locking position, is located between the guide element (40), which is attached to the door leaf, and the guide rail (20).